

# Material Safety Data Sheet

Page: 1 of 3

Infosafe No. YSY3B Issue Date : May 2006 APPROVED by PLESSJAL

Product Name : EASIPOL

Classified as hazardous according to criteria of NOHSC

## COMPANY DETAILS

**Company Name** Peerless Jal Pty Ltd (ABN 53 006 489 345)  
**Address** 10-12 Raglan Street Preston  
Victoria 3072 Australia  
**Tel/Fax** Tel: (03) 9416 6700 Fax: (03) 9416 8516  
**Other Information** The information in this MSDS was obtained from sources which we believe are reliable. However, the information is provided without warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the material are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising from or in any way connected with the handling, storage, use or disposal of the material.

## IDENTIFICATION

**Product Code** LP06  
**Product Name** EASIPOL  
**UN Number** 1993  
**DG Class** 3  
**Packing Group** II  
**Hazchem Code** 3[Y]E  
**Poisons Schedule** S5  
**Product Use** For use on linoleum, sealed wood floors and furniture.

## Physical Data

**Appearance** Yellow/Orange thixotropic dispersion with solvent odour.  
**Boiling Point** 147 - 199°C (@ 760mm Hg)  
**Vapour Pressure** Not determined  
**Specific Gravity** 0.810 ± 0.005  
**Flash Point** 30°C (closed cup)  
**Flamm. Limit LEL** 0.9% (for white spirits)  
**Flamm. Limit UEL** 7.0% (for white spirits)  
**Solubility in Water** Insoluble

## Other Properties

**Volatile Component** 10.0 - 11.0%  
**Viscosity** Semi paste

## Ingredients

Ingredients	Name	CAS	Proportion
	Micro, macro and polyethylene waxes	N/A	10-60 %
	Dyes and thickeners	N/A	0-10 %
	Anti slip agents	N/A	0-10 %
	Mineral spirits	8042-75-5	82%

## HEALTH HAZARD INFORMATION

### Health Effects

**Acute - Swallowed** Harmful, may cause lung damage. Ingestion can result in vomiting and depression.  
**Acute - Eye** A severe eye irritant.  
**Acute - Skin** Slightly irritating due to defatting nature. Prolonged or repeated exposure

# Material Safety Data Sheet

Page: 2 of 3

Infosafe No. YSY3B Issue Date : May 2006 APPROVED by PLESSJAL

Product Name : EASIPOL

Classified as hazardous according to criteria of NOHSC

**Acute - Inhaled** may lead to dermatitis.  
Concentrated vapour of solvent may cause headaches and dizziness and in severe cases uncoordination.

## First Aid

**Swallowed** If swallowed, do NOT induce vomiting. Give a glass of water. If poisoning occurs, contact a doctor or the Poisons Information Centre, Phone 13 11 26.

**Eye** Hold eyelids open and flood with water for at least 15 minutes and see a doctor.

**Skin** Remove contaminated clothing and wash affected area with soap and water.

**Inhaled** Remove to fresh air. If breathing has stopped, give artificial respiration and call a doctor.

## Advice to Doctor

## Other Health Hazard Information

## PRECAUTIONS FOR USE

**Exposure Limits** TLV 100ppm max recommended (White Spirits).

**Eng. Controls** Ventilation: Air circulation from open doors or windows is adequate, especially in high ceiling buildings such as gymnasiums and stadiums. In small poorly ventilated or enclosed areas, mechanical extraction ventilation or an approved organic vapour respirator is recommended.

## Personal Protection

**Protective Equip.** Avoid contact with skin and eyes.  
Splash proof goggles, coveralls, and viton gloves are recommended when handling. In confined poorly ventilated area an approved organic respirator is recommended.

## Flammability

**Fire Hazards** Flammable liquid.  
Keep away from heat, sparks or naked flames.

## SAFE HANDLING INFORMATION

## Storage and Transport

**Transport** Classified according to the Transport of Dangerous Goods (ADG) Code and the Standards for the Uniform Scheduling of Drugs and Poisons.

**Special Shipping Information** Correct Shipping Name: Flammable Liquid, N.O.S. (Contains: White Spirits)

**Storage and Transport** Store in well-ventilated areas. Store away from heat, ignition sources and strong oxidizing agents.  
Transport in accordance with 'The Australian Code for the Transport of Dangerous Goods by Rail or Road', for class 3 chemicals.

**ADR/RID UN Number (Road Transport)** 1993

## Spills and Disposal

**Spills & Disposal** Eliminated all ignition sources. Remove leaking containers to detached area. Cover with absorbent material and dispose to an approved Hazardous waste facility.

## Fire/Explosion Hazard

**Fire/Explos. Hazard** Extinguish small fires with Foam, Dry Chemicals or CO2.  
Can readily form flammable mixtures at or above Flashpoint (30°C).  
Firefighters must use self-contained breathing apparatus in confined or poorly ventilated spaces. Cool intact storage drums with water spray.

**Hazchem Code** 3[Y]E

## OTHER INFORMATION

# Material Safety Data Sheet

Page: 3 of 3

Infosafe No.	YSY3B	Issue Date : May 2006	APPROVED by PLESSJAL
--------------	-------	-----------------------	----------------------

Product Name : **EASIPOL**

Classified as hazardous according to criteria of NOHSC

---

**Other Information** ID No.: LP06-06

---

## CONTACT POINT

---

...End Of MSDS...