

Information contained on this Product Information Data Sheet is to the best of our knowledge accurate and reliable. However, no guarantee is given nor intended as conditions of handling and use of this product are beyond our control.

STRIP OFF

FLOOR STRIPPER

TDST25-1-1100

DESCRIPTION: -

STRIP OFF is a heavy-duty floor stripper formulated to remove heavily burnished or high build-ups of metal cross-linked sealer finishes with minimum labour. STRIP OFF is safe for use on all resilient floors and quickly softens and emulsifies old worn and discoloured finishes for ease of removal.

STRIP OFF must not be used to remove sealer finishes from sealed timber floors as it may affect the timber seal, requiring sanding to rectify the floor.

STRIP OFF is 100% volatile and therefore does not leave chemicals on the floor that could affect seals or finishes that are to be applied after stripping.

PHYSICAL PROPERTIES	
Appearance	Clear water white liquid
Odour	Glycol
pH	11.5 – 12.5
Specific Gravity	0.990 ± 0.005
Percentage Volatiles	100%
Solubility in Water	Infinite

DIRECTIONS FOR USE: -

STRIP OFF can be diluted up to 1 part to 2 parts with warm water, or used neat as supplied dependent upon build-up.

Apply STRIP OFF liberally to the floor with a cotton mop ensuring the entire floor surface is thoroughly wet. Work in small controllable area sizes. Allow 5 - 10 minutes contact and then scrub with a slow speed rotary scrubber or Automatic Scrubber fitted with stripping pads in larger areas take care not to allow the stripper to dry off. After scrubbing, pick up the slurry, rinse with clean water and allow to dry. On drying inspect the floor and repeat the stripping process on any areas not completely stripped.

NOTE:

During the emulsification process most floors become very slippery.

Care should be taken when working on wet floors.

STRIP OFF can be diluted up to 1 part to 2 parts with warm water, or used neat as supplied dependent upon build-up.

THE CLEANERS WAREHOUSE

68 Booth Street ANNANDALE NSW . TEL: (02) 9660 5000 FAX: (02) 9660 5765.

