

# Material Safety Data Sheet

Page: 1 of 3

Infosafe No. 1PJ2P Issue Date : September 2008 APPROVED by PLESSJAL

Product Name : STRIP OFF

Classified as hazardous according to criteria of NOHSC

## COMPANY DETAILS

**Company Name** Cleaners Ware House (ABN 59 002 516 289)

**Address**  
68 Booth St  
68 Booth St  
68 Booth St  
68 Booth Street Annandale  
New South Wales 2038 Australia

**Emergency Tel.** (02) 9660 5000

**Tel/Fax**  
Tel:  
(02) 9660 5000  
Fax:  
(02) 9660 5765

**Emergency Contact Address**  
Technical Department  
10-12 Raglan Street  
Preston  
VIC 3072  
Tel: (03) 9416 6700  
Fax: (03) 9416 8516

## IDENTIFICATION

**Product Name** STRIP OFF

<b>Other Names</b>	<b>Name</b>	<b>Product Code</b>
	LAZER FLOOR STRIPPER	ST25

**UN Number** 1760

**DG Class** 8

**Packing Group** II

**Hazchem Code** 2X

**Poisons Schedule** S5

**Product Use** To remove aged or dirty water based seals, polishes and waxes from vinyl tiles and sheeting and linoleum.

## Physical Data

**Appearance** Water white liquid of Glycol odour.

**Boiling Point** 105°C (@ 760mm Hg)

**Vapour Pressure** Not determined.

**Specific Gravity** 0.999 ± 0.005

**Flash Point** Non flammable.

**Flamm. Limit LEL** Not applicable.

**Flamm. Limit UEL** Not applicable.

**Solubility in Water** Infinite.

## Other Properties

**Volatile Component** 100%

**pH Value** 11.5 - 12.5

**Form** Liquid

## Ingredients

<b>Ingredients</b>	<b>Name</b>	<b>CAS</b>	<b>Proportion</b>
	Perfume	N/A	0-10 %
	Ethanolamine	141-43-5	0-10 %
	Industrial Ethanol	64-17-5	0-10 %
	Ethylene glycol butyl ether	111-76-2	0-10 %
	Water	N/A	To 100%

# Material Safety Data Sheet

Page: 2 of 3

Infosafe No. 1PJ2P Issue Date : September 2008 APPROVED by PLESSJAL

Product Name : **STRIP OFF**

Classified as hazardous according to criteria of NOHSC

## HEALTH HAZARD INFORMATION

### Health Effects

**Acute - Swallowed** Can result in nausea, vomiting and stomach pain.  
**Acute - Eye** Slight pain, moderate irritation and possible corneal injury.  
**Acute - Skin** Irritant due to defatting nature of the product. Repeated or prolonged contact may cause dermatitis.  
**Acute - Inhaled** Inhalation of concentrated vapour may cause nose, mouth and throat irritation.

### First Aid

**Swallowed** Do NOT induce vomiting. Give a glass of water and contact a doctor or the Poisons Information Centre. Phone 13 11 26.  
**Eye** Hold eyelids open and flood with water for at least 15 minutes & see a Doctor.  
**Skin** Remove contaminated clothing, (launder before re-use) and wash affected area with soap & water.  
**Inhaled** Remove to fresh air. Rinse mouth and nasal passage with water.

### Advice to Doctor

**Advice to Doctor** Treat symptomatically.

### Other Health Hazard Information

## PRECAUTIONS FOR USE

**Exposure Limits** LD50 470mg/Kg for Ethylene glycol butyl ether.  
Ethylene glycol ether OSHA standard 50ppm & ACGIH 25ppm.  
TLV for Ethanol 1000ppm.  
**Eng. Controls** Ventilation: No special requirements.

### Personal Protection

**Protective Equip.** Avoid contact with skin and eyes.  
Wear impervious gloves while handling or pouring.  
Wear goggles or safety glasses and protective footwear while pouring or diluting.

### Flammability

**Fire Hazards** Non flammable.

## SAFE HANDLING INFORMATION

### Storage and Transport

**Transport** Classified according to the Transport of Dangerous Goods (ADG) Code and the Standards for the Uniform Scheduling of Drugs and Poisons.  
**Special Shipping Information** Correct Shipping Name: Corrosive Liquid N.O.S. (Contains: Amine)  
**Other Transport Info.** This MSDS summarises our best knowledge of health and safety hazard information of the product and how to safely handle and use the product.  
**ADR/RID UN Number (Road Transport)** 1760

### Spills and Disposal

**Spills & Disposal** Avoid secondary accidents, floors may become slippery. Pick up excess for disposal and rinse residue with water.  
**Disposal** Consign to chemical dump by licensed chemical waste hauler to be disposed of within local authority laws.

### Fire/Explosion Hazard

**Fire/Explos. Hazard** Presents no known fire or explosive hazards and forms no known hazardous decomposition products.

# Material Safety Data Sheet

Page: 3 of 3

Infosafe No.	1PJ2P	Issue Date : September 2008	APPROVED by PLESSJAL
--------------	-------	-----------------------------	----------------------

Product Name : **STRIP OFF**

Classified as hazardous according to criteria of NOHSC

---

**Hazchem Code**      Treat fire for materials actually involved in the fire.  
2X

---

## OTHER INFORMATION

---

**Risk Statement**      R36/37/38 Irritating to eyes, respiratory system and skin.  
**Safety Statement**    S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.  
**Hazard Category**      Irritant  
**Other Information**    ID No.: ST25

---

## CONTACT POINT

---

**Technical Contact Point**      Technical Department  
10-12 Raglan Street  
Preston  
VIC 3072  
Tel: (03) 9416 6700  
Fax: (03) 9416 8516  
...End Of MSDS...